Safety Data Sheet

Trade Name: DRY-RITE Drying Agent

1.0	Commercial Product Name and Supplier			
1.1	Commercial product name / designation	Dry-Rite Drying Agent		
1.2 1.2.2	Application / Use SIC	Dental material for use by dental professionals. 851 Human health activity		
1.2.3	Use Category	55		
1.3	Manufacturer			
	Pulpdent Corporation 80 Oakland Street, P.O. Box 780 Watertown, MA 02472 USA	Telephone: 1 617 9 Email: <u>Pulpdent@p</u>	26-6666 / Fax: 1 617 9 <u>ulpdent.com</u>	26-6262
1.4	Emergency Telephone Number	1-800-535-5053 (24	Hour / USA)	
1.5	Authorized European Representative	Advena Limited Tower Business Centre, 2nd Floor, Tower Street, Swatar, BKR 4013 Malta		
	UK Responsible Person	Advena Limited Pure Offices, Plato Close Warwick, CV34 6WE United Kingdom		
	CH Authorized Representative	MedEnvoy Switzerland Gotthardstrasse 28, 6302 Zug, Switzerland		
2.0	Hazards Identification			
2.1	Classification			
2.1.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Hazard Class	Hazard Category	Hazard Statement
		Flammable liquid	2	H225
		Eye irritation	2	H319
		STOT SE	3	H335
		Skin irritation	2	H315; EUH066
2.1.2	Classification according to Directive 67/548/EEC (See SECTION 16 for full text of risk phrases)	Flammable (F) R1 ² Irritant (Xi) R36 / 3 ²		

2.2 GHS Label Elements

Hazard Pictograms





Signal Word: **DANGER**

Restricted to use by dental professional only

Hazard Statements:

H225: Highly flammable liquid and vapor. Category 2. H319: Causes serious eye irritation. Category 2.

H335: Specific Target Organ Toxicity (STOT), single exposure, respiratory tract, Category 3: May cause respiratory irritation.

H315: Causes skin irritation. Category 2.

Safety Data Sheet

Trade Name: DRY-RITE Drying Agent

EUH066: Repeated exposure may cause skin dryness or cracking.

Precautionary Statements:

P210: Keep away from heat, sparks, open flame, hot surfaces. No smoking.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P261: Avoid breathing fumes.

P280: Wear protective gloves/ clothing and eye protection.

P304+P340: If inhaled, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Revision Date: June 14, 2022

P303+P361+P353: If on skin or hair, remove contaminated clothing. Rinse skin with water.

P370+P378: In case of fire, use dry chemical, alcohol foam, or carbon dioxide for extinction.

3.0	Composition				
3.1	Chemical charac	cterization of the prep	paration:	Denatured ethyl alco	hol preparation.
3.2	Hazardous ingre	Hazardous ingredients			
	CAS Number	Name of the Ingredient	Concentration	Classification per 67/548/EEC	Classification per Regulation (EC) No.1272/2008 (CLP).
	64-17-5	Ethyl alcohol	92%	Flammable (F); Irritant (Xi). R11- 36/ 37/38-66	Flammable liquid, Category 2 Eye irritation, Category 2 STOT SE, Category 3 Skin irritation Category 2.
	67-64-1	Acetone (denaturant)	7%	Flammable (F); Irritant (Xi). R11- 36/ 37/38-66	Flammable liquid, Category 2 Eye irritation, Category 2 STOT SE, Category 3 Skin irritation Category 2.
4.0	First Aid Measures				
4.1	General Information		tract if inhaled lassitude, app	I. Exposure to ethanol >	on contact. May cause irritation of respiratory 1000 ppm may cause headache, drowsiness, afety data sheet to medical personnel. Get atty.
4.2	Eye Contact		Keep eyelids	Keep eyelids apart, flush with running water for 15+ minutes. Get medical attention.	
4.3	Skin Contact			aminated clothing. Imme Get medical attention if	ediately wash with soap, running water. Use irritation persists.
4.4	Ingestion Rinse mouth with water. Do not induce von Never give anything by mouth to an uncon		e vomiting. Get immediate medical attention. unconscious person.		
4.5				Move to fresh air. If necessary, administer oxygen and/or artificial respiration; seek medical attention.	
4.6	Precautions for first responders Ventilate the area.		area. Wear safety glass	. Wear safety glasses and gloves.	
4.7	.7 Information for physicians				
	Symptoms Contact wi			material may cause irrita	ation or redness in eyes or on skin. Inhalation ct.

Pulpdent Corporation

Safety Data Sheet

Trade Name: **DRY-RITE Drying Agent**

	Hazards	Exposure to ethanol >1000 ppm may cause headache, drowsiness, lassitude, appetite loss. Persons with chronic respiratory or skin disease are at increased risk with prolonged and/or repeated contact.	
	Treatment	Same as above under First Aid	
5.0	Fire Fighting Measures		
5.1	Suitable extinguishing media	Use dry chemical, alcohol foam, or carbon dioxide. Water may be ineffective, but should be used to keep fire-exposed containers cool.	
5.2	Extinguishing media to avoid	Water may be ineffective, but will keep fire-exposed containers cool.	
5.3	Special exposure hazards in a fire	Carbon monoxide, carbon dioxide from incomplete combustion	
5.4	Special protective equipment for fire-fighters	Self-contained breathing apparatus.	
6.0	Accidental Release Measures		
6.1	Personal precautions.	Wear chemical splash goggles and gloves.	
6.2	Environmental precautions	Avoid releasing large quantities into environment.	
6.3	Method for clean up	Ventilate area. Wear safety glasses, lab coat, gloves. Wipe up with absorbent material (paper or cloth towels). Rinse area of spill with water. Place all material in closed container away from heat, sparks, sun and oxidizers.	
7.0	Handling and Storage		
7.1	Handling	Remove applicator tip and recap immediately after use. Do not use in presence of ignition sources. Take same precautions when container is emptied, as residual product is hazardous.	
7.2	Storage	Keep tightly capped in original container. Store at cool room temperature in a well-ventilated area. Avoid extreme temperatures (>27°C/80°F, <5°C/40°F), sparks, direct sunlight, oxidizing agents. Vapor may form flammable mixtures with air.	
7.3	Specific uses	Dental drying agent	
8.0	Exposure Controls / Personal Protection		
8.1	Exposure limit values	Ethanol: 1000 ppm; Acetone: 750 ppm	
8.2	Exposure controls		
8.2.1	Occupational exposure controls	No special equipment or ventilation required under normal conditions of use. For large quantities/prolonged exposure, use enclosure, local ventilation, dilution to reduce concentration below TLV.	
8.2.1.1	Respiratory protection	Good general ventilation is sufficient to control any airborne vapors.	
8.2.1.2	Hand protection	No special requirements other than surgical gloves.	
8.2.1.3	Eye protection	No special requirements other than safety glasses.	
8.2.1.4	Skin protection	No special requirements other than good hygiene and safety practices.	
8.2.1.5	Other controls	Emergency eye wash fountain should be close by. Wash hands after use. Do not eat, drink or smoke.	
8.2.2	Environmental exposure controls	Follow all government regulations.	

Pulpdent Corporation Safety Data Sheet

Trade Name: **DRY-RITE Drying Agent**

9.0	Physical and Chemical Properties	
9.1	Characteristics	
9.1.1	Appearance /Color / Physical state	Pink, transparent liquid
9.1.2	Odor	Characteristic, sweet, ethanol odor
9.2	Important health, safety and environmental information	
9.2.1	рН	Not applicable
9.2.2	Boiling point	Boiling Point: 173°F / 78.3°C
9.2.3	Flash point	43°F / 6°C (Tag closed cup)
9.2.4	Ignition temperature	423°C
9.2.5	Explosive properties	LEL: 3.3; UEL: 19
9.2.6	Odor threshold	159 ppm
9.2.7	Vapor pressure	44.6 mm Hg / 59 mbar / ld: E
9.2.8	Specific gravity	0.795
9.2.9	Solubility in water	Complete
9.2.10	Partition coefficient	Not determined
9.2.11	Viscosity	Not determined
9.2.12	Vapor density	1.59
9.2.13	Evaporation rate	Not determined
10.0	Stability and reactivity	
10.1	Conditions to avoid	Heat, sparks, open flame, any ignition source.
10.2	Materials to avoid	Acetyl chloride and a wide range of oxidizing agents.
10.3	Hazardous decomposition products	Carbon monoxide, carbon dioxide from incomplete combustion.
10.4	Further information	Stable if stored and used as directed.
11.0	Toxicological information	
11.1	Acute toxicity	Minimal health hazard under normal conditions of use. Ethanol: LD_{50} in young rats: 10.6 g/kg orally; LD_{50} in old rats: 7.06 g/kg orally. Acetone: LD_{50} in rats: 10.7 ml/kg orally
11.2	Irritation and corrosiveness	May cause irritation/redness of eyes or skin on contact. May cause irritation of respiratory tract if inhaled.
11.3	Sensitization	Not applicable.
11.4	Sub-acute, sub-chronic and prolonged toxicity	No chronic health hazard under normal conditions of use.
11.5	Carcinogenicity, Mutagenicity, Reproductive Toxicity	Not a carcinogen under normal conditions of use. Large quantities of ethanol, ingested over time, may be carcinogenic or a cause of Fetal Alcohol Syndrome. IARC has reported a relationship between habitual drinking of significant quantities of alcoholic beverages and cancer of oral cavity, pharynx, esophagus, liver.

Trade Name: **DRY-RITE Drying Agent**

11.6	Empirical data	None available
11.7	Clinical experience	Dry-Rite and similar products have been used in dentistry for decades with no reported problems.
12.0	Ecological Information	
12.1	Ecotoxicity	Follow good work practices and government regulations. Avoid release into environment.
13.0	Disposal Considerations	
13.1	Regulations	Follow all local and national government regulations in disposing material or contaminated packaging.
14.0	Transport Information	
14.1	UN Number	1170
14.2	Technical name	Ethyl alcohol
14.3	Packing group	II
14.4	IATA class	3
15.0	Regulatory Information	
15.1	EU	Class I medical device under the Medical Devices Regulation (EU) 2017/745
15.2	US FDA	Class II medical device
15.3	Health Canada	Class I medical device
16.0	Other information	
16.1		
10.1	List of relevant R phrases	R11: Highly flammable. R36/37/38: Irritating to eyes, respiratory system and skin. R66: Repeated exposure may cause skin dryness or cracking.
16.2	List of relevant R phrases Hazard Statements	

Pulpdent Corporation

Safety Data Sheet

Trade Name: **DRY-RITE Drying Agent**

16.4	Restrictions on use	Pulpdent dental materials, such as Dry-Rite, are to be sold to and used by dental professionals only.
16.5	Further information	The information presented herein is believed to be factual as it has been derived from the works of persons believed to be qualified experts. However, nothing contained in this information is to be taken as a warranty or representation for which Pulpdent Corporation bears legal responsibility. The user should review any recommendations in the specific context of the intended use to determine whether they are appropriate.
16.6	Sources of key data	National Institute for Occupational Safety (NIOSH)
		US Occupational Safety and Health Administration (OSHA)
		Eur-Lex European Union Law: Regulation (EC) No. 1272/2008 (CLP) and Regulation (EC) No. 1907/2006 (REACH).
		Guidance on the compilation of safety data sheets. Version 1.1; December 2011. European Chemicals Agency
16.7	Information which has been added, deleted or revised.	This Safety Data Sheet has been revised to meet the requirements of the GHS SDS format, Regulations (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH). Specifically, Sections 2.1, 2.2, 3.2, 16.2, 16.3 have been modified.

Revision Date: June 14, 2022