


**Safety Data Sheet**Trade Name: **PULPDENT FLOWS-RITE™**

1.0 Commercial Product Name and Supplier																		
1.1	Commercial product name / designation	<b>Flows-Rite™ Multi-Purpose Flowable Composite &amp; Veneer Cement</b>																
1.2	Application / Use	Dental material for use by dental professional only.																
1.2.2	SIC	851 Human health activity																
1.2.3	Use Category	55																
1.3	Manufacturer	<b>Pulpdent Corporation</b> 80 Oakland Street, P.O. Box 780 Watertown, MA 02472 USA Telephone: 1 617 926-6666 / Fax: 1 617 926-6262 Email: <a href="mailto:Pulpdent@pulpdent.com">Pulpdent@pulpdent.com</a>																
1.4	Emergency Number	24 Hour Emergency: 1-800-535-5053 (USA)																
1.5	Authorized European Representative	Advena Limited Tower Business Centre, 2nd Floor, Tower Street, Swatar, BKR 4013 Malta																
	UK Responsible Person	Advena Limited Pure Offices, Plato Close Warwick, CV34 6WE United Kingdom																
	CH Authorized Representative	MedEnvoy Switzerland Gotthardstrasse 28, 6302 Zug, Switzerland																
2.0 Hazards Identification																		
2.1	Classification	Irritant.																
2.1.1	Classification according to Regulation (EC) No 1272/2008 [CLP]	<table border="1"> <thead> <tr> <th>Hazard Class</th> <th>Hazard Category</th> <th>Hazard Statement</th> </tr> </thead> <tbody> <tr> <td>Eye irritation</td> <td>2</td> <td>H319</td> </tr> <tr> <td>STOT SE</td> <td>3</td> <td>H335</td> </tr> <tr> <td>Skin irritation</td> <td>2</td> <td>H315</td> </tr> <tr> <td>Skin sensitization</td> <td>1</td> <td>H317</td> </tr> </tbody> </table>	Hazard Class	Hazard Category	Hazard Statement	Eye irritation	2	H319	STOT SE	3	H335	Skin irritation	2	H315	Skin sensitization	1	H317	
Hazard Class	Hazard Category	Hazard Statement																
Eye irritation	2	H319																
STOT SE	3	H335																
Skin irritation	2	H315																
Skin sensitization	1	H317																
2.1.2	Classification according to Directive 67/548/EEC (See SECTION 16 for full text of risk phrases)	Irritant; Xi; R 36/37/38 - 43																
2.2	<b>GHS Label Elements</b>																	
	Hazard Pictograms																	
																		
	Signal Word: <b>WARNING</b>																	
	<b>Restricted to use by dental professional only.</b>																	
	<b>Hazard Statements</b>																	
	H319: Eye irritation. 2. May cause eye irritation.																	
	H335: STOT SE. 3. May cause respiratory irritation.																	
	H315: Skin irritation. 2. May cause skin irritation.																	
	H317: Sensitization. 1. May cause an allergic skin reaction.																	

## Safety Data Sheet

Trade Name: **PULPDENT FLOWS-RITE™**

### Precautionary Statements

P261: Avoid breathing vapor.

P280: Wear protective gloves and eye protection

P305+P351: If in eyes, rinse cautiously with water for several minutes.

P337+P313: If eye irritation persists, get medical advice/attention.

P302+P352: If on skin, wash with plenty of soap and water.

P333+P313: If irritation or rash occurs, get medical advice/attention.

P410+P411: Protect from sunlight. Store at temperature not exceeding 27°C / 80°F.

---

**Safety Data Sheet**Trade Name: **PULPDENT FLOWS-RITE™**

<b>3.0 Composition</b>																
3.1	Chemical characterization of the preparation      Glass filler materials in methacrylate resins.															
3.2	Hazardous ingredients															
	<table border="1"> <thead> <tr> <th>CAS Number</th> <th>Name of the Ingredient</th> <th>Concentration</th> <th>Classification per 67/548/EEC</th> <th>Classification per Regulation (EC) No.1272/2008 (CLP)</th> </tr> </thead> <tbody> <tr> <td>Proprietary</td> <td>Uncured methacrylate ester monomers</td> <td>55-65%</td> <td>Xi (Irritant), R36/37/38; R43</td> <td>Eye irritation, 2, H319 STOT SE 3, H335 Skin irritation, 2, H315 Skin sensitization, 1, H317</td> </tr> <tr> <td>112945-52-5</td> <td>Amorphous silica</td> <td>5 %</td> <td>Xi (Irritant), R36/37/38</td> <td>Eye irritation, 2, H319 STOT SE 3, H335 Skin irritation, 2, H315</td> </tr> </tbody> </table>	CAS Number	Name of the Ingredient	Concentration	Classification per 67/548/EEC	Classification per Regulation (EC) No.1272/2008 (CLP)	Proprietary	Uncured methacrylate ester monomers	55-65%	Xi (Irritant), R36/37/38; R43	Eye irritation, 2, H319 STOT SE 3, H335 Skin irritation, 2, H315 Skin sensitization, 1, H317	112945-52-5	Amorphous silica	5 %	Xi (Irritant), R36/37/38	Eye irritation, 2, H319 STOT SE 3, H335 Skin irritation, 2, H315
CAS Number	Name of the Ingredient	Concentration	Classification per 67/548/EEC	Classification per Regulation (EC) No.1272/2008 (CLP)												
Proprietary	Uncured methacrylate ester monomers	55-65%	Xi (Irritant), R36/37/38; R43	Eye irritation, 2, H319 STOT SE 3, H335 Skin irritation, 2, H315 Skin sensitization, 1, H317												
112945-52-5	Amorphous silica	5 %	Xi (Irritant), R36/37/38	Eye irritation, 2, H319 STOT SE 3, H335 Skin irritation, 2, H315												
<b>4.0 First Aid Measures</b>																
4.1	General Information      May be irritating to eyes, respiratory system and skin. Do not inhale vapors. May cause sensitization by skin contact. Show this safety data sheet to medical personnel. Seek medical attention in case of uncertainty.															
4.2	Inhalation      Move to fresh air. If necessary, administer oxygen, artificial respiration and seek medical attention.															
4.3	Skin Contact      Take off contaminated clothing. Wash skin thoroughly with soap and running water for 15 minutes.															
4.4	Eye Contact      Keep eyelids apart and flush with running water for 15+ minutes. Seek medical attention.															
4.5	Ingestion      Rinse mouth with water. Do not induce vomiting. Seek immediate medical attention. May be irritating to mucous membranes.															
4.6	Precautions for first responders      Ventilate the area. Wear eye and skin protection.															
4.7	Information for physicians															
	Symptoms      Irritation or redness in eyes, throat or on skin.															
	Hazards      May be irritating to eyes, respiratory system and skin. May cause sensitization by skin contact.															
	Treatment      As above under First Aid.															
<b>5.0 Fire Fighting Measures</b>																
5.1	Suitable extinguishing media      Carbon dioxide, dry chemical, alcohol foam, or water fog. Water spray may be used to keep fire exposed containers cool.															
5.2	Extinguishing media to avoid      Do not use direct water stream															
5.3	Special exposure hazards in a fire      Heat may cause polymerization with rapid release of energy, especially in amounts greater than in this product.															
5.4	Special protective equipment for fire-fighters      Self-contained breathing apparatus															
<b>6.0 Accidental Release Measures</b>																
6.1	Personal precautions.      Ventilate area. Wear safety glasses, gloves, and lab coat.															
6.2	Environmental precautions      Contain uncured, spilled material. Cured/set-up material is, to our knowledge, inert. Follow all government regulations.															
6.3	Method for clean up      Wipe up spill with paper towels or cloths. Collect for disposal in a covered container. Wash area of spill with alcohol or soap and water.															

**Safety Data Sheet**Trade Name: **PULPDENT FLOWS-RITE™**

<b>7.0</b>	<b>Handling and Storage</b>	
7.1	Handling	Follow good hygiene practices. Remove applicator tip from syringe; cap container immediately after use. Keep light cure materials shaded from intense light sources.
7.2	Storage	Store product tightly capped in original container at cool room temperature (<25°C). Avoid direct/strong light, ignition sources, temperature extremes (>27°C/80°F, <5°C/40°F). Shelf life for unopened product is two years from date of manufacture, provided that the material has been stored properly.
7.3	Specific uses	Dental restorative material
<b>8.0</b>	<b>Exposure Controls / Personal Protection</b>	
8.1	Exposure limit values	PEL: Not established. TLV: Not established.
8.2	Exposure controls	
8.2.1	Occupational exposure controls	No special equipment required under normal conditions of use.
8.2.1.1	Respiratory protection	Good general ventilation will control airborne vapors.
8.2.1.2	Hand protection	Usual surgical gloves will limit contact with uncured material.
8.2.1.3	Eye protection	Usual safety glasses
8.2.1.4	Skin protection	Good personal hygiene, safety practices; wearing a lab coat.
8.2.1.5	Other controls	Nearby emergency eye wash fountain. Wash hands after use.
8.2.2	Environmental exposure controls	Cure material before disposing.
<b>9.0</b>	<b>Physical and Chemical Properties</b>	
9.1	Characteristics	
9.1.1	Appearance /Color / Physical state	Tooth-colored paste
9.1.2	Odor	Faint, characteristic
9.2	Important health, safety and environmental information	
9.2.1	pH	Not determined
9.2.2	Boiling point	Not determined
9.2.3	Flash point	Not determined
9.2.4	Flammability (solid, gas)	Not applicable
9.2.5	Explosive properties	Not applicable
9.2.6	Oxidizing properties	Not determined
9.2.7	Vapor pressure	< 1 mm Hg / 133 Pa / Id: B
9.2.8	Specific gravity	1.930
9.2.9	Solubility in water	Nil
9.2.10	Partition coefficient	Not determined
9.2.11	Viscosity	Not determined
9.2.12	Vapor density	Not determined
9.2.13	Evaporation rate	Not determined
<b>10.0</b>	<b>Stability and reactivity</b>	

**Safety Data Sheet**Trade Name: **PULPDENT FLOWS-RITE™**

10.1	Conditions to avoid	Avoid temperature extremes (>80°F / 27°C, <40°F / 5°C/), intense light, moisture, contamination.
10.2	Materials to avoid	Reducing and oxidizing agents, peroxides, amines.
10.3	Hazardous decomposition products	Under fire conditions and with amounts far greater than that supplied in this product, hazardous polymerization may occur with heat build up and release of carbon monoxide, carbon dioxide, and oxides of nitrogen.
10.4	Further information	Stable if stored and used as directed. Polymerization will occur when light-cured material is exposed to direct light.
<b>11.0</b>	<b>Toxicological information</b>	
11.1	Acute toxicity	Not toxic. Minimal health hazard in the quantities present in this product and under normal conditions of use.
11.2	Irritation and corrosiveness	May be irritating to eyes, mucous membranes or skin on contact or with prolonged exposure.
11.3	Sensitization	May be sensitizing. Prolonged or frequent skin contact may cause allergic skin reactions in some susceptible individuals.
11.4	Sub-acute, sub-chronic and prolonged toxicity	Prolonged and/or frequent skin contact may cause allergic skin reactions in susceptible individuals. Prolonged exposure to large amounts (more than in this product) of this material may cause eye and respiratory irritation.
11.5	Carcinogenicity, Mutagenicity, Reproductive Toxicity	None known
11.6	Empirical data	Not available
11.7	Clinical experience	Flows-Rite has been used safely and effectively for more than 15 years without any reports of adverse events.
<b>12.0</b>	<b>Ecological Information</b>	
12.1	Ecotoxicity	Avoid release of uncured material into the environment. To the best of our knowledge, polymerized material is inert. No other information is available. Follow all government regulations.
<b>13.0</b>	<b>Disposal Considerations</b>	
13.1	Regulations	Follow all local and national government regulations in disposing material or contaminated packaging.
<b>14.0</b>	<b>Transport Information</b>	
14.1	Restrictions	None. Not regulated.
<b>15.0</b>	<b>Regulatory Information</b>	
15.1	EU	Class IIa medical device under MDD 93/42/EEC.
15.2	US FDA	Class II medical device
15.3	Health Canada	Class III medical device
<b>16.0</b>	<b>Other information</b>	
16.1	List of relevant R phrases	R36/37/38, Irritating to eyes, respiratory system and skin. R43, Sensitizing by skin contact.
16.2	Hazard Statements	H319: Eye irritation. Hazard category 2.

**Safety Data Sheet**Trade Name: **PULPDENT FLOWS-RITE™**

		H335: Specific Target Organ Toxicity - Single exposure; hazard category. 3. Respiratory tract irritation. H315: Skin irritation. Hazard category 2. H317: Skin Sensitization. Hazard category 1.
16.3	Precautionary Statements	P261: Avoid breathing vapor. P280: Wear protective gloves and eye protection P305 + P351: If in eyes, rinse cautiously with water for several minutes. P337 + P313: If eye irritation persists, get medical advice/attention. P302 + P352: If on skin, wash with plenty of soap and water. P333 + P313: If irritation or rash occurs, get medical advice / attention. P410 + P411: Protect from sunlight. Store at temperature not exceeding 27°C / 80°F.
16.4	Restrictions on use	Pulpdent products are to be sold to and used by dental professionals only.
16.5	Further information	The information presented herein is believed to be factual as it has been derived from the works of persons believed to be qualified experts. However, nothing contained in this information is to be taken as a warranty or representation for which Pulpdent Corporation bears legal responsibility. The user should review any recommendations in the specific context of the intended use to determine whether they are appropriate.
16.6	Sources of key data	National Institute for Occupational Safety (NIOSH) US Occupational Safety and Health Administration (OSHA) Eur-Lex European Union Law: Regulation (EC) No. 1272/2008 (CLP) and Regulation (EC) No. 1907/2006 (REACH). Guidance on the compilation of safety data sheets. Version 1.1; December 2011. European Chemicals Agency
16.7	Information which has been added, deleted or revised.	This Safety Data Sheet has been revised to meet the requirements of the GHS SDS format and Regulations (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH). Specifically, Sections 2.1, 2.2, 3.2, 16.2, 16.3 have been modified.

---